

TUBE 3200 W

NEW



96>98
CRI


RGBA
wWcW

2800 K
6500 K

Helium & Air

Technical data

Light source	LED RGBAwWcW
CCT	2800 K to 6500 K
CRI	96>98
TCLI	98+
LED lifetime	50,000 h
Power supply (PSU)	110-240 VAC 50-60 Hz
Nb Power supply unit	4
Power supply dimensions	37 x 15 x 7 cm / 14 x 6 x 3 in
Power supply weight	5,7 kg / 12.5 lb
Power consumption	3200 W
IP Protection	IP65
Noise level	Noiseless
Mesh network balloons	100 m (109 yd) between each balloon



Light controls



- > via the **control panel on the product**
- > Remotely via the **Airstar Light app**
- > **DMX**
 - DMX profiles available for major control surfaces
 - 5-pin DMX connectors & **CRMX**

Airstar Light App

Control your balloons easily and remotely!



Control up to 250 balloons



8 light animations available



Packaging

Flight case
Dimensions: 120 x 60 x 74 cm
47 x 24 x 29 in
Transport gross weight: 95 kg (210 lb)



Included accessories

Guy rope set, skirt, 20 m extension, helium cylinder connection

Envelope

Envelope dimensions	281 x 500 cm / 110,6 x 196,8 in
Volume	33,4 m ³ / 1179,5 ft ³
Net weight of the balloon	23,6 kg / 52 lb
Certifications	CE, IP65



Illumination




Height 7,5 m (24.5 ft)



	0	1	2	3	4	5	6	7	8	9	10	m
3200 K	358	342	338	309	272	234	198	163	136	114	94	lux
	33,2	31,7	31,4	28,7	25,3	21,7	18,4	15,1	12,6	10,6	8,8	fc
5600 K	376	382	366	334	294	253	212	176	146	122	101	lux
	34,9	35,5	34,0	31,0	27,3	23,5	19,7	16,3	13,5	11,3	9,4	fc



Tube

 Air or Helium Filled



	Hybrid	Options	
		Warm White	Cold White
Power	1.8 kW LED	1.8 kW LED	1.8 kW LED
Colour temperature	1800 W: 4300 K 2 x 900 W: from 2700 K to 6500 K	3200 K	5600 K
Envelope dimensions	Ø 2.20 m 7.2 ft L 4 m 13 ft	Ø 2.20 m 7.2 ft L 4 m 13 ft	Ø 2.20 m 7.2 ft L 4 m 13 ft
Helium Volume	16.2 m ³ 572 ft ³	16.2 m ³ 572 ft ³	16.2 m ³ 572 ft ³
DMX	Yes	Yes	Yes
Available accessories	Skirts x 4	Skirts x 4	Skirts x 4

	Hybrid	Options	
		Warm White	Cold White
Power	3.6 kW LED	3.6 kW LED	3.6 kW LED
Colour temperature	3600 W: 4300 K 2 x 1800 W: from 2700 K to 6500 K	3200 K	5600 K
Envelope dimensions	Ø 2.85 m 9.3 ft L 5 m 16 ft	Ø 2.85 m 9.3 ft L 5 m 16 ft	Ø 2.85 m 9.3 ft L 5 m 16 ft
Helium Volume	33.4 m ³ 1.179,5 ft ³	33.4 m ³ 1.179,5 ft ³	33.4 m ³ 1.179,5 ft ³
DMX	Yes	Yes	Yes
Available accessories	Skirts x 4	Skirts x 4	Skirts x 4